

AIP DENMARK

AD 2. AERODROMES**1. Aerodrome Location Indicator and Name:****EKYT - Aalborg****2. Aerodrome Geographical and Administrative Data**

1. ARP PSN and site at AD:	57 05 34.04N 009 50 56.99E	5. AD ADM:	Aalborg Lufthavn a.m.b.a
2. Distance and direction from city:	3.5 NM NW of Aalborg	AD address:	Aalborg Airport Lufthavnsvej 100 DK-9400 Nørresundby
3. ELEV:	10 FT	TEL:	+45 98 17 11 44 (AD)
REF temperature:	19.3°C	FAX:	+45 99 33 17 75 (TWR/APP)
4. MAG VAR:	1.5°E (JUL 2010)	E-mail:	+45 98 17 36 84 (AD/ARO/Briefing)
Annual change:	Increasing: 10'	AFS:	+45 99 33 17 79 (TWR/APP)
			aalborg.airport@aal.dk
		6. Types of traffic permitted:	EKYT
			IFR/VFR

7. Remarks: NIL

3. Operational Hours

1. AD:	Daily 0500-2230 (0400-2130)	7. ATS:	H24 (H24)
2. Customs and immigration:	The airport is open for traffic to/from all States. Hours for customs clearance and immigration as for AD.	8. Fuelling:	100LL -self-service only - daily 0500-2230 (0400-2130). Jet A1 - daily 0500-2100 (0400-2000). - SAT 0500-2000 (0400-1900) For fuel outside opening hours, contact Aalborg Airport Office. Please note that an extra fee will be charged.
3. Health and sanitation:	NIL	9. Handling:	As AD
4. AIS Briefing Office:	Daily 0500-2100 (0400-2000)	10. Security:	As AD
5. ATS Reporting Office (ARO):	Daily 0500-2100 (0400-2000)	11. De-icing:	As AD
6. MET Briefing Office:	As AD		

12. Remarks: Outside stated hours PPR submitted to airport office not later than 2100 (2000), and for ambulance flights 1 HR PN to TWR, TEL: +45 99 33 17 75

4. Handling Services and Facilities

1. Cargo-handling facilities:	Yes	5. Hangar space for visiting aircraft:	No
2. Fuel and oil types:	Fuel: 100LL. Jet A1. Oil: Nil	6. Repair facilities for visiting aircraft:	Minor repairs only
3. Fuelling facilities and capacity:	100LL: 300 L/MIN Jet A1: 900 L/MIN	7. Remarks:	a. Frequency used for handling: 131.550 - call sign "Aalborg Handling" b. Hydraulic oil not available c. Jet A1 Daily 0500-2100 (0400-2000)
4. De-icing facilities:	De-icing fluid and equipment		

5. Passenger Facilities

1. Hotels:	Hotels in town	5. Bank and Post Office:	Cash dispenser only (Major credit cards accepted)
2. Restaurants:	Yes	6. Tourist Office:	In Aalborg TEL +45 98 12 60 22 +45 98 12 63 55 FAX +45 98 16 69 22
3. Transportation:	Taxi. Bus in connection with regular scheduled traffic.		
4. Medical facilities:	Hospital in Aalborg		

7. Remarks: NIL

6. Rescue and Fire Fighting Services

1. AD category for fire fighting:	CAT 7 and boats	3. Capability for removal of disabled aircraft:	-
2. Rescue equipment:	-		

4. Remarks: Rescue and fire fighting services available within AD hours except for the first 30 minutes.

7. Seasonal Availability - Clearing

- | | | | |
|--------------------------------|---------------------------------|--------------------------|---------------------------------|
| 1. Type of clearing equipment: | See snow plan in section AD 1.2 | 2. Clearance priorities: | See snow plan in section AD 1.2 |
|--------------------------------|---------------------------------|--------------------------|---------------------------------|
3. Remarks: AD available all seasons.

8. Aprons, Taxiways and Check Locations Data

- | | | | |
|---|---|---|---|
| 1. Apron surface and strength: | Concrete/Asphalt
In front of passenger terminal:
PCN 42/R/D/X/U
Other parts of apron:
PCN 39/R/D/X/U
Composite construction | 3. ACL and ELEV: | At civil apron 8 FT |
| 2. Taxiway width, surface and strength: | TWY A: 23 M
TWY B: 15 M
TWY C, D, and E: 22 M
Concrete/Asphalt
TWY C: PCN 42/R/D/X/U
Other TWY: PCN 39/R/D/X/U
Composite construction | 4. VOR checkpoints:
INS checkpoints: | -
See Aircraft Parking/Docking Chart |
5. Remarks: NIL

9. Surface Movement Guidance and Control System and Markings

- | | | | |
|---|--|--------------------------|--|
| 1. Aircraft stand ID signs, Taxi guide lines, Visual docking / parking guidance system: | See item 20 - Local Traffic Regulations and Aircraft Parking/Docking Chart | 2. RWY and TWY markings: | RWY 08L/26R:
THR, RWY NR, TDZ, centre line, side stripes

RWY 08R/26L:
THR, RWY NR, centre line, side stripes

TWY:
Centre line, side stripes, holding position |
| | | 3. Stop bars: | - |
4. Remarks: NIL

10. Aerodrome Obstacles

In approach/TKOF areas			In circling area and at AD	
a	b	c	a	b
RWY/ Area affected	Obstacle type Elevation Markings/LGT	PSN	Obstacle type Elevation Markings/LGT	PSN
-			-	

Remarks: All obstacles are marked by day and night

11. Meteorological Information Provided

- | | | | |
|--|--|---|---|
| 1. Associated MET Office: | Aalborg
TEL +45 98 19 56 63 | 6. Flight documentation: | Charts. Abbreviated plain language texts. |
| 2. Hours of service: | MON-THU 0630-1430 (0530-1330)
FRI 0630-1300 (0530-1200)
EXC HOL | Language(s) used: | English and Danish |
| Outside Hours: | Central Forecasting Office (VTC)
TEL +45 39 15 72 72 | 7. Charts and other information available: | Surface analysis (current chart)
Upper air analysis (current chart)
Prognostic upper air chart
Significant weather chart
Satellite cloud pictures
Weather radar pictures |
| 3. Office responsible for TAF preparation:
Periods of validity: | Aalborg within hours of service, otherwise
MET Centre Karup
24 hours | 8. Supplementary equipment available: | - |
| 4. Type of landing forecast:
Interval of issuance: | TREND

Period of issuance
MON-THU 0630-1430 (0530-1330)
FRI 0630-1300 (0530-1200)
EXC HOL | 9. ATS units provided with information: | APP/TWR |
| 5. Briefing/Consultation provided: | Self briefing and telephone consultation | 10. Additional information (limitation of service, etc.): | - |

AIP DENMARK

12. Runway Physical Characteristics

RWY	Direction	RWY dimensions	Strength (PCN), Surface of RWY and SWY (SFC friction Calibration NR)	THR PSN	THR ELEV/ Highest ELEV of TDZ of precision APCH RWY
08L	083.3° GEO 081.8° MAG	2654 x 45 M	PCN 64/R/D/X/U Concrete/Asphalt Composite construction	57 05 37.37N 009 50 00.17E	7 FT/-
26R	263.3° GEO 261.8° MAG	2654 x 45 M	PCN 64/R/D/X/U Concrete/Asphalt Composite construction	57 05 47.44N 009 52 36.75E	10 FT/-
08R	083.3° GEO 081.8° MAG	2549 x 22.5 M	PCN 52/F/D/X/U Asphalt	57 05 30.87N 009 50 07.71E	7 FT/-
26L	263.3° GEO 261.8° MAG	2549 x 22.5 M	PCN 52/F/D/X/U Asphalt	57 05 40.51N 009 52 38.08E	10 FT/-

RWY	RWY-SWY slope	SWY dimensions	CWY dimensions	Strip dimensions	Obstacle-free zone
08L	less than 1 %	-	-	2774 x 300 M	-
26R	less than 1 %	-	-	2774 x 300 M	-
08R	less than 1 %	-	-	2669 x 300 M	-
26L	less than 1 %	-	-	2669 x 300 M	-

Remarks: Runway classification RWY NR RUNWAY CODETYPE

08L	4C	PA-1
08R	2B	NINST
26L	2B	NINST
26R	4C	PA-2

13. Declared Distances

RWY	TORA	TODA	ASDA	LDA	Remarks
<u>RWY 08L</u>				2654 M	-
<u>TWY E/F</u>	2654 M	2654 M	2654 M		
<u>TWY D/G</u>	2070 M	2070 M	2070 M		
<u>TWY C/H</u>	1220 M	1220 M	1220 M		
<u>RWY 26R</u>				2654 M	-
<u>TWY A/K</u>	2654 M	2654 M	2654 M		
<u>TWY B/J</u>	2070 M	2070 M	2070 M		
<u>TWY C/H</u>	1430 M	1430 M	1430 M		
<u>RWY 08R</u>				2549 M	-
<u>TWY E</u>	2549 M	2549 M	2549 M		
<u>RWY 26L</u>				2549 M	-
<u>TWY A</u>	2549 M	2549 M	2549 M		

14. Approach and Runway Lighting

RWY	APCH LGT: Type Length Intensity	THR LGT: Colour WBAR	PAPI: Angle MEHT	TDZ LGT: Length	RWY centre line LGT: Length Spacing Colour Intensity	RWY edge LGT: Length Spacing Colour Intensity	RWY end LGT: Colour WBAR	SWY LGT: Length Colour
08L	470 M White LIH	Green	2.75°	-	2650 M 15 M Standard colour LIH	2650 M White LIH	Red	-
26R	CAT II 900 M LIH	Green	2.75°	900 M White	2650 M 15 M Standard colour LIH	2650 M White LIH	Red	-
08R	150 M White LIL Crossbar 150 M from THR	Green	2.75°	-	-	2550 M LIL	Red	-
26L	150 M White LIL Crossbar 150 M from THR	Green	2.75°	-	-	2550 M LIL	Red	-

Remarks: NIL

15. Other Lighting and Secondary Power Supply

1. ABN/IBN location, characteristics and hours of operation:	ABN on TWR BLDG, FLG W every 2.5 SEC, operating when aircraft are expected at night or in poor visibility by day	3. TWY edge and centre line LGT:	Blue edge, LIL. RGL for RWY 08L/26R
2. LDI location and LGT:	-	4. Secondary power supply/switch-over time:	Yes, switch-over time CAT II MAX 1 SEC, otherwise MAX 15 SEC
Anemometer location and LGT:	-		

5. Remarks: NIL

16. Helicopter Landing Area

NIL

17. ATS Airspace

1. Designation and lateral limits:	AALBORG CTR 57 08 38N 009 33 55E - 57 08 58N 009 39 55E - 57 12 28N 009 46 25E - 57 12 58N 009 53 55E - 57 10 28N 010 01 25E - 57 10 48N 010 06 55E - 57 02 48N 010 08 55E - 57 02 28N 010 03 15E - 56 58 58N 009 56 45E - 56 58 28N 009 49 10E - 57 01 08N 009 41 25E - 57 00 48N 009 35 55E - 57 08 38N 009 33 55E.	2. Vertical limits:	1500 FT MSL/GND
		3. Airspace classification:	D
		4. ATS unit call sign: Language(s):	AALBORG TOWER EN, DA
		5. Transition altitude:	3000 FT MSL

6. Remarks: NIL

18. ATS Communication Facilities

Service	CS	Channels/ Frequencies	HR	Remarks
TWR	AALBORG TOWER	118.300 284.775 257.800 121.500 243.000	H24	DOC: 4000 FT/25 NM MIL MIL Emergency Emergency
ATIS	AALBORG AIRPORT INFORMATION	120.475	H24	DOC: FL 200/60 NM Language: EN
PSR MSSR		2750/2855 1030		DOC: FL 250/50 NM Radar 4 DOC: FL 450/250 NM Radar 4
	AALBORG APP/TWR			Radar 4/ From multi radar track from ACC København

19. Radio Navigation and Landing Aids

FAC ILS CAT VAR	ID	Channel/ Frequency	HR	PSN	DME ELEV	Remarks
LLZ 26R CAT II	YT	109.900 MHZ	HO	57 05 35.97N 009 49 38.62E		ILS class II/D/4
GP 26R		333.800 MHZ	HO	57 05 50.45N 009 52 21.82E		Angle 2.75°, RDH 35 FT
DME 26R	YT	CH 36x	HO	57 05 50.20N 009 52 21.87E	18.7 FT	FREQ paired with LLZ 08L and 26R
VOR 1°E 2008	AAL	116.700 MHZ	H24	57 06 13.39N 009 59 44.08E		DOC: FL 500/100 NM DME INFO from TACAN AAL
TACAN 1°E 2008	AAL	CH 114x	H24	57 06 14.16N 009 59 34.11E	56.8 FT	DOC FL 500/200 NM
LLZ 08L CAT I	AE	109.900 MHZ	HO	57 05 49.02N 009 53 01.40E		ILS class I/D/4
GP 08L		333.800 MHZ	HO	57 05 42.19N 009 50 13.42E		Angle 2.75°, RDH 37 FT
DME 08L	AE	CH 36x	HO	57 05 50.20N 009 52 21.87E	18.7 FT	FREQ paired with LLZ 08L and 26R
L	GL	398 KHZ	H24	57 05 03.80N 009 40 53.20E		DOC 20 NM

20. Local Traffic Regulations

1. Parking

TWR will allocate aircraft stand or parking area for arriving civil flights. Aircraft shall normally park without marshaller assistance. Marshaller assistance can be obtained from Aalborg Airport Office on frequency 131.550.

Parking stand 1, 2, 3, 4 and 5 are marked with number, guidelines and stoplines.

General Aviation parking and other parking areas are not marked. Due to security regulations, General Aviation pilots and passengers are not allowed to leave the aircraft unless a Marshall is present. Therefore all aircraft parked at the General Aviation parking area and refueling area, must contact the Airport Office (ARO) on frequency 131.550 for Marshall assistance. As Marshall can be occupied elsewhere, some waiting time can be expected. Therefore contact the Airport Office as soon as possible during approach.

Refueling is not permitted without advising the Airport Office.

2. Flight Plan

1.1 For all departing flights a complete flight plan or an abbreviated flight plan shall be submitted to the ATS reporting office at Aalborg before taxiing.

3. Exit from stand 1 - 5

Aircraft taxiing on the apron has to coordinate this with Aalborg Tower (118.300 MHz) before commencing taxi. To minimize blast on terminal,

reduce power to idle after break away.

Aircraft leaving the stand, by own power shall obtain start up approval and taxi instruction from Aalborg Tower (118.300 MHz). Aircraft requiring push-back shall obtain push-back approval from Aalborg Tower (118.300 MHz). Aircraft has to be connected to push-back truck and in contact with driver of push-back truck before requesting push-back approval from the tower. Push back is compulsory for departing A/C from stand 2-5 for aircraft type A319/320/321, B737-3/5/7/9 and MD80/90, if similar or larger A/C is parked on the stand to the right.

4. Use of auxiliary power unit (APU)

Use of APU on aircraft stands shall be limited as far as possible.

APU may be used:

- 5 minutes after on block.
- 5 minutes before leaving apron.

Exemptions:

When the outside air temperature (OAT) is below -10°C or above +25°C APU may be used as follows, unless otherwise instructed by marshall:

- 5 minutes after on block.
- 15 minutes before leaving apron.

Engine run-ups may only take place on test sites assigned by ATS reporting office (VHF 131.550 Mhz)

21. Noise Abatement Provisions

1. General Provisions

1.1 The noise abatement provisions may be deviated, if the Air Traffic Controller or the Pilot-in-Command judges it necessary for safety reasons.

1.2 Violation of the noise abatement provisions can be punished in pursuance of the Regulation for Civil Aviation BL 3-40 "Abatement of Noise from Controlled Aerodromes".

2. Jet aircraft

2.1 In connection with approach to landing, a minimum height of 2300 FT shall be observed over greater Aalborg.

2.2 Take-off restrictions:

2.2.1 RWY 08L/R:

a. Turn must not be commenced until having passed 2 NM on radial 262 of AAL VOR/DME.

2.2.2 RWY 26L/R:

a. Turn to the South must not be commenced until having passed 2000 FT

2.3 School and training flights with A/C with MTOW > 20.000 kg. will only be allowed if prior permission (PPR) has been obtained from the Airport Office. Permission will only be given, in very special cases and will never be given for flights in weekends, holiday periods and evening/night times.

School- and training flights are not allowed outside normal opening hours 2230-0500 (2130-0400)

3. Propeller and turboprop aeroplanes

3.1 No restrictions.

4. Helicopters

4.1 No restrictions.

5. Reporting

5.1 Reporting by the Air Navigation Services Aalborg to the Civil Aviation Administration, Department of Safety Regulations.

5.1.1 The Air Navigation Services Aalborg shall notify the Department of Safety Regulations of every clearance deviating from the above mentioned provisions.

5.1.2 The Air Navigation Services Aalborg shall notify the Department of Safety Regulations of every clearance according to the provision in item 1.1.

5.1.3 The Air Navigation Services Aalborg shall notify the Department of Safety Regulations of every operation where it is observed, that it is carried out contrary to the clearance issued according to the provisions in item 2.2 on take-off restrictions.

5.2 Aalborg Lufthavn (Aalborg Airport) reporting to the Department of Safety Regulations.

5.2.1 Aalborg Lufthavn (Aalborg Airport) shall notify the Department of Safety Regulations when it has been ascertained that school or training flights have taken place against the provision in item 2.3.

5.3 The Civil Aviation Administration, Department of Safety Regulations follow-up of reports.

5.3.1 The Department of Safety Regulations will make further investigation based on the received reports. The investigation will include an evaluation of whether liability to punishment shall be exercised according to Regulations for Civil Aviation BL 3-40.

22. Flight Procedures

1. IFR Arrival

1.1 Aircraft will normally be cleared by ACC KØBENHAVN to AALBORG HOLDING.

1.2 Radio Communication failure

Navigation aid designated for radio communication failure during IMC for arriving aircraft is VOR/DME AAL.

1.3 Precision Approach. Category II Operations

The operations are subject to the following procedures and conditions:

a. ATC procedures.

ATC will apply special safeguards and procedures during Category II operations. These procedures will only be introduced when the ceiling is 200 FT or less and/or RVR 800 M or less.

The minimum distance between an aircraft on final approach carrying out a Category II ILS approach and any other preceding aircraft will not be less than 5 NM. The separation must be established at the latest when preceding aircraft passes THR.

Departing aircraft must have commenced take-off run before arriving aircraft has left 2000 FT on final approach.

b. Pilot procedures.

Pilots who intend to carry out a Category II ILS approach are to use the following phrase: "Request Category II ILS approach runway 26R".

Above mentioned request shall be made to COPENHAGEN CONTROL and confirmed on first contact with AALBORG APPROACH.

2. IFR Departure

2.1 Standard Instrument Departures

Standard Instrument Departures (SID) have not been established.

2.2 Omnidirectional departures

RWY 08L/R and 26R/L: Climb straight ahead to at least 600 FT MSL before turn is commenced.

3. VFR Flights

3.1 VFR reporting points, VFR holdings and VFR routes are established, see ANC 1:500 000 - Denmark. Aircraft established in EGHOLM VFR holding, must not hold north of the coastline west of Aalborg City.

23. Additional Information

1. MIL jet aircraft

1.1 MIL jet aircraft execute right hand pattern to RWY 26R

2. Arrestor Cables

2.1 Arrestor cables for military aircraft may be suspended across:

- RWY 08L, 450 M prior to runway end
- RWY 26R, 450 M prior to runway end
- RWY 08R, 450 M prior to runway end
- RWY 26L, 450 M prior to runway end

Cables disengaged in approach end.

3. Parachuting

3.1 Parachuting may take place.

4. Gliding and hanggliding

4.1 Glider/Hang-glider areas within Aalborg TMA, see AD 2. EKYT, Glider Areas in TMA

4.2 VFR-flights may obtain information as to whether a glider/hang-glider area is active on the relevant APPROACH frequency

A request for a clearance to pass an active area will normally be complied with, but VFR-flights which have been cleared to pass an active area will not receive traffic information and advice to avoid collision as prescribed for airspace class D.

4.3 IFR-flights will be separated from active glider/hang-glider areas. However, if an area is allocated for an individual flight, IFR-flights will be separated from such flight only and not from the whole area.

Note: Observe the fact that gliding and hang gliding may take place above and below the areas in airspace class E and G, whether the areas are active or not.

24. Charts related to the Aerodrome

Chart type

Aerodrome Chart-ICAO

Aircraft Parking/Docking Chart-ICAO

Precision Approach Terrain Chart-ICAO

Instrument Approach Chart-ICAO

Chart title

ADC

APDC

PATC 26R

ILS/DME 08L

L+DME 08L

ILS/DME 26R (CAT I+II)

VOR/DME 26R

Glider Areas in TMA

Other Charts